

PUT `ddl/database/:db/table/:existingtable/like/:newtable`

Table of contents

1 Description.....	2
2 URL.....	2
3 Parameters.....	2
4 Results.....	2
5 Example.....	3

1 Description

Create a new HCatalog table like an existing one

2 URL

`http://www.myserver.com/templeton/v1/ddl/database/:db/table/:existingtable/like/:newtable`

3 Parameters

Name	Description	Required?	Default
:db	The database name	Required	None
:existingtable	The existing table name	Required	None
:newtable	The new table name.	Required	None
group	The user group to use when creating a table	Optional	None
permissions	The permissions string to use when creating a table.	Optional	None
external	Allows you to specify a location so that Hive does not use the default location for this table.	Optional	false
ifNotExists	If true, you will not receive an error if the table already exists.	Optional	false
location	The HDFS path	Optional	None

The [standard parameters](#) are also supported.

4 Results

Name	Description
table	The new table name
database	The database name

PUT ddl/database/:db/table/.existingtable/like/:newtable

5 Example

Curl Command

```
% curl -s -X PUT -HContent-type:application/json -d {} \
'http://localhost:50111/templeton/v1/ddl/database/default/table/test_table/like/
test_table_2?user.name=ctdean'
```

JSON Output

```
{
  "table": "test_table_2",
  "database": "default"
}
```